

Wire Rope Hoist

Hoist for Crane

Stonimage supplies Wire Rope Hoist designed as M5 or M6 Grade based on F.E.M, DIN, EN standard, capacity range from 0.5tons to 12.5tons to equip overhead crane, jib crane, I-beam and special lifting system. It owns high safety system through the reliable structure, overload limiter, height limiters. Low clearance from hook to roller, galvanized rope, low noise motor makes the hoist safety, high efficient, free-maintenance and clean surface.



F.E.M | DIN | EN Standard

Capacity (t)	Lifting Height of Hoist (mm)	Working Grade	Lifting Speed (m/min)	Traveling Speed (m/min)	Beam Width (mm)	Hoist Length (mm)	Hoop up Limit (mm)	Max Wheel Pressure (kN)	Weight (kg)
1.6	6,000	M5	1.6/10	2~20	200~300	930	400	6.1	300
	9,000					400	6.2	335	
	12,000					400	6.3	370	
2.5	6,000	M5	0.8/5.0	2~20	200~350	1180	430	9.1	315
	9,000					430	9.2	350	
	12,000					430	9.3	385	
3.2	6,000	M5	0.8/5.0	2~20	250~350	1180	450	11.5	335
	9,000					450	11.6	370	
	12,000					450	11.7	405	
6.3	6,000	M5	0.8/5.0	2~20	300~450	1170	500	22	400
	9,000					500	22.1	450	
	12,000					500	22.2	500	
8.0	6,000	M5	0.8/5.0	2~20	300~450	1120	650	28	580
	9,000					650	28.1	610	
	12,000					650	28.2	640	
10.0	6,000	M5	0.8/5.0	2~20	300~450	1120	650	34.7	580
	9,000					650	34.8	610	
	12,000					650	34.9	640	
10.0	6,000	M5	0.66/4.0	2~20	300~450	1140	700	34.7	650
	9,000					700	34.8	690	
	12,000					700	34.9	730	
12.5	6,000	M5	0.66/4.0	2~20	300~500	1140	700	43.3	660
	9,000					700	43.4	700	
	12,000					700	43.5	740	

Note: pls send email to inquire@stonimage.com when the lifting height is more than 12meters or need a customised design.

